

The Twister XL₃

The TWISTER XL 3™ is a motorized back-pack ULV sprayer designed to take the weight and stress off of the operators hand and wrist to ensure ease and comfort when working. Ideal for controlling mosquitoes and other flying insects the variable chemical output capability make the TWISTER XL 3™ suitable for all situations.



The TWISTER XL 3™ features the **Tanaka Purefire** engine, a radically new design of 2 cycle engine which gives unequalled fuel efficiency coupled with a level of emissions so low as to exceed all current or anticipated hydrocarbon emission regulations.

The DYNA-FOG® MICROTEC™ nozzles will produce 90% of the droplets below 20 microns when used at the recommended flow rates. This meets the requirements of all current chemical labels for controlling flying insects. When the high flow rate is discharged through a single nozzle the TWISTER XL 3™ will produce larger droplets of 50 microns suitable for applying a residual deposit to vegetation and any other surface.

The TWISTER XL3™ is built from only the highest quality materials. Coated with chemical resistant epoxy paint, this unit will give reliable usage with the very minimum of maintenance. Backed by DYNA-FOG'S® 1 year warranty.

TWISTER XL 3 Standard Features:

- Two cycle Tanaka PureFire™ engine.
- Engine quick cut-off switch.
- 3 stage high output rotary blower.
- All formulation controls at operators hand.
- Small frame size and adjustable padded shoulder and waist straps to suit all body sizes.
- Single nozzle produces precise droplet size. Double nozzle head is optional..
- Visual warning pennant on 26" telescopic mast.
- Fuel mixing beaker and funnel included.
- Flow meter to determine the viscosity value of individual formulations.
- 1 year warranty**

TWISTER XL3 Specifications:

- ENGINE:** Tanaka 2 cycle, 40cc, 2.2 HP low-emission, high performance engine.
- BLOWER:** Belt driven, high speed rotary, 3 stage steel shaft - 95 cfm at 3 psi.
- NOZZLES:** Single MICROTEC™ nozzle. Twin nozzle unit optional.
- OUTPUT** (at 7500 rpm w/water:
Single nozzle: 1.5oz./min up to 3.3oz./min.
Twin nozzles: 12.0 oz./min.
- TANKS:** made from HDPE
Formulation = 1 gal. Fuel: =33 floz.
- FUEL MIX:** 50:1 (50 parts gas: 1 part oil)
- SPECS:** 15"W x 12"D x 22.5"H , 26lbs.



Nixalite® of America Inc.
1025 16th Avenue East Moline, IL. 61244
Experts In Architectural Bird Control Since 1950

Phone: 800.624.1189 or 309.755.8771
Fax: 800.624.1196 or 309.755.0077
Email: birdcontrol@nixalite.com
Web: www.nixalite.com



Where the World Shops for Humane Bird and Animal Control.

Copyright© 2010 by Nixalite® of America Inc. All rights reserved. Nixalite® is a registered trademark of Nixalite® of America Inc. Printed with pride in the USA.