

Trailblazer Pulse-Jet Thermal Fogger



Big machine performance in a compact, easy to handle package

The Trailblazer electric start pulse-jet thermal fogger is designed to dispense both oil and water based solutions for a wide variety of applications.

All Trailblazers feature DynaFog's 12 volt electric starting system to assure reliability, fuel efficiency and ease of operation.

The Trailblazer unique design produces a high output thermal fog with virtually no carbon monoxide, making it ideal for indoor as well as outdoor applications.

The Trailblazer engine is made from highly specialized stainless steel, while the formulation tanks are made from rugged chemical resistant polyethylene for years of trouble free operation.

Trailblazer pulse jets can dispense water and oil based insecticides, fungicides, germicides, mold abatement solutions, disinfectants, bird repellents and odor elimination products.

Use the Trailblazer in greenhouses, warehouses, factories, food processing plants, parks, campgrounds, live stock and poultry containment, mill granaries, restaurants, parking garages and much more.

Pulse-jet foggers can help you control flying insects such as mosquitoes, black flies, gnats and locust. This in turn helps prevent the spread of diseases like encephalitis, dengue, typhus, yellow fever and malaria.



Standard Features

- 24 hp resonant pulse principle engine.
- Revolutionary electric starting system.
- All formulation controls at operators hand.
- Puts out 30,000 cuft of fog per minute.
- Fogs oil and water based solutions.
- Powered by batteries or a 12v battery.
- Low exhaust gases make it ideal for indoor and outdoor applications.
- 1 year limited warranty
- Ideal for insect control, plant hydration, odor control, mold abatement etc.
- Comes complete with instruction manual, 8 - 1.5v batteries, auxiliary start cable and 2 clean-out brushes.

Specifications

Model: 2600 E
Engine: Resonant pulse principle
Performance: 24 hp/hour or 18 kw/hour
Fuel Type: Gasoline
Fuel Consumption: 0.3 US G/Hr - 1.1 L/hr
Fuel Tank: Corrosion resistant - 0.85 Qts or 0.8 L
Formulation Output: 0-5 G/hr, or 0-19 L/hr
Produces up to 30,000 cu.ft. of fog per minute
Droplet Size: 0.5 - 50 microns
Formulation Container: 1 Gal or 3.8 L
Power Supply: 8 - 1.5 V "D" size alkaline batteries. Any 12 V DC vehicle battery (connects to cigarette lighter receptacle with supplied auxiliary cable).
Overall Dimensions: 32"L x 14"W x 21"H
Total Weight: 41 lbs / 18.6 Kg



Nixalite® of America Inc.
1025 16th Avenue East Moline, IL. 61244
Experts In Architectural Bird Control Since 1950

Phone: 800.624.1189 or 309.755.8771
Fax: 800.624.1196 or 309.755.0077
Email: birdcontrol@nixalite.com
Web: www.nixalite.com



Where the World Shops for Humane Bird and Animal Control.